

### DS-2CD6986F-H

#### 8 MP Multi-Imager Panoramic Dome Camera

- Panoramic Camera
- Up to 8 MP Resolution (4 x 2 MP Sensors)
- 1/1.8" Progressive Scan CMOS
- 4 x 5 mm Fixed Lenses
- 180° Horizontal View (Stitched Image)
- Ultra-Low Light, Slow Shutter
- 1 Edge Storage MicroSD Slot, 128 GB
- 24 VAC/PoE+ (802.3at)
- Audio/Alarm I/O
- IP66 and IK10 Protection
- Heater and Fan



The Hikvision DS-2CD6986F-H 8 MP Multi-Imager Panoramic Dome Camera offers a full 180 degree view, stitched together from its four 2 MP cameras.

Four 5 mm lenses provide an ultra-wide image to address the most demanding situations. A maximum resolution of 4096 x 1800 means high detail at up to 30 frames per second (fps). A built-in microSD/SDHC/SDXC slot that supports up to 128 GB provides on-board storage.

The DarkFighter Series ultra-low light Smart cameras are able to capture high quality color images in dim light environments. DS-2CD6986F-H offers full HD resolution with PoE, defog, and 3D DNR to meet a wide variety of applications.






IK10 and IP66 certifications protect the camera from impact and inclement weather.

**Available Models:** DS-2CD6986F-H



DS-2CD6986F-H	
<b>Camera</b>	
Image Sensor	1/ 1.8" progressive scan CMOS
Minimum Illumination	Color: 0.002 lux @ f/1.4 AGC on; B/W: 0 lux with IR
Shutter Speed	1/25s to 1/100,000s
Slow Shutter	Yes
Lens	5 mm x 4, pan: 180°, tilt 78.4°
Angle Adjustment	Pan: 0° to ~360°, tilt: 45° to ~90°
Lens Mount	CS
Day/Night	IR cut filter with auto switch/schedule/triggered by alarm
WDR	Digital
<b>Compression Standards</b>	
Video Compression	H.264/MJPEG
H.264 Type	Baseline/Main/High Profile
Video Bit Rate	32 Kbps to 16 Mbps
Dual Streams	Yes
Audio Compression	G.711 (64 Kbps)/G.722.1 (16 Kbps)/G.726 (16 Kbps)/MP2L2 (32 to 192 Kbps)/AAC/PCM (16 to 64 Kbps)
<b>Image</b>	
Maximum Resolution	4096 x 1800
Frame Rate	Mode 1: Main Stream: 30 fps (4096 x 1800, 3840 x 1680) Sub Stream: 30 fps (704 x 320) Mode 2: Main Stream: 24 fps (2400 x 3840), 30 fps (1200 x 1920) Sub Stream: 30 fps (480 x 768, 320 x 512)
Image Settings	Saturation, brightness, contrast, sharpness adjustable by client software or Web browser
Back Light Compensation	Yes, zone configured
Region of Interest (ROI)	Yes, 4 regions
Digital Noise Reduction	3D DNR
Defog	Yes
<b>Network</b>	
Network Storage	NAS (supports NFS, SMB/CIFS), ANR
Alarm Triggers	Motion detection, tamper alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
Security	Three level user authentication, password authorization, HTTPS and SSH certificate, IEEE802.1X, basic and digest authentication, watermark, IP address filtering, log-in lockout
Standards	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
<b>Interface</b>	
Communication	1 RJ-45 10M/100M Ethernet port, RS-485 interface
On-Board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Alarm	1x I/O (up to 24 VDC 1A or 110 VAC 500 mA)
Audio	1 x 3.5 mm jack, audio in (mic in/line in)/out interface
<b>General</b>	
Operating Conditions	-30° C to 60° C (-22° F to 140° F), humidity 95% or less (non-condensing)
Power Supply	24 VAC ±10%, PoE+ (802.3at) UL/cUL Listed
Power Consumption	Maximum 22 W
Protection Level	IEC60068-275Eh, 20J; EN50102, up to IK10, IP66
Dimensions	Φ7.68" × 6.26" (Φ195 mm × 159 mm)
Weight	2850 g (6.28 lbs)

## Accessories

				
<b>WML</b> Long Wall Mount w/Back Box	<b>PC210</b> Pendant Cap	<b>CM</b> Corner Mount	<b>PM</b> Pole Mount	<b>Conduit Base</b> Included with Camera

## Dimensions

